

# ShanPu

### Illuminated Tactile Switches Series SPL









#### General Specifications

Circuit Current Rating Contact Resistance Insulation Resistance Operating Force Total Travel Mechanical Life Operating Temperature :-25  $^{\circ}$ C  $\sim$  +60  $^{\circ}$ C

:SPST :50mA @ 12VDC

:100mOhm Max.(initial) :100MOhm Min.  $:300gf \pm 100gf$ 

:0.3mm±0.1mm :5,000,000 cycles Min.

#### Materials

Cover Cap Housing Base Lamp Term.

Act. Dome End Term. LED


:Polycarbonate (PC) :Polycarbonate (PC)

:Polyamide (PA) :Polyamide (PA) :Phosphor bronze (PBS) with gold plating

:SUS with silver plating :Brass with gold plating :Surface Mount Chip LED

PAT. M 332927 PAT. ZL 2007 2 0311508.9

### Dimension (SPLG)




EXAMPLE: SPLG1YCS0024 (h1) 8.0mm + (h3) 5.0mm = (h)13.0mm

### How to order (SPLG)


#### SPLG LED Colors Red CAP Page 23 Super Yellow White Pure Green Blue Page 36 EXAMPLE:



### Contact configuration



PCB Layout




(SPST) **Contact Configuration** 



## ShanPu

## Illuminated Tactile Switches Series SPL





# ShanPu

## Illuminated Tactile Switches Series SPL

